

NOTES:

- 1. BEVEL: REMOVE SHARP EDGES.
- 2. SURFACE FLATNESS: 3-4 WAVES
- 3. SURFACE QUALITY: SCRATCH:DIG 20:10 OVER ACTIVE AREA
- 4. PARALLELISM: < 30 ARCSEC
- 5. PATTERN OVERALL DIMESIONAL ACCURACY: 0.00004" (0.001MM)
- 6. PATTERN TO BE CENTERED ON SUBSTRATE ±0.004" (±0.10MM)
- 7. PATTERN LINEWIDTH IS 0.001" ±0.0001" (0.0254MM ±0.0025MM)
- 8. PATTERN ORIENTATION: RIGHT READING LOOKING THROUGH
- COATING: LOW REFLECTION CHROMIUM FIRST SURFACE. CHROMIUM ADHESION LAYER WITH A TOP LAYER OF CHROMIUM OXIDE, OPTICAL DENSITY > 3.0. COATING DESIGNED TO PROVIDE REFLECTION < 5% @ 550 NM
- 10. PATTERN: HALF SOLID BAR, HALF BRACKET GAUGE. 13 LINEWIDTHS: 0.04MM THROUGH 0.10MM IN 0.01MM INCREMENTS, 0.15MM THROUGH 0.40MM IN 0.5MM INCREMENTS.
- 11. PACKAGING: BAG AND TAG PER 700MLA0060-001
- 12. PATTERN DIAMETER: 14.321MM

MLO PART NUMBER: AA006		EDMUND P/N: 32519		ONLINE CATALOG	RD2055
TOLERANCES (EXCEPT AS NOTED)	MAX LEVY AUTOGRAPH				
DECIMAL .XXX= +/005 .XX= +/015 .X= +/030	SODA LIMI	E GLASS	SCALE NONE	DRAWN BY TE	N
+/030	THICKNESS GAUGE .04 TO .40MM				
angular +/-0.5Deg.	12-12-00	drawing number 3001	VILA	A0072A-	006