

- 3. SURFACE QUALITY: SCRATCH:DIG 20:10 OVER ACTIVE AREA
- 4. PARALLELISM: < 30 ARCSEC
- 5. PATTERN OVERALL DIMESIONAL ACCURACY: 0.00004" (0.001MM)
- 6. PATTERN TO BE CENTERED ON SUBSTRATE ±0.004" (±0.10MM)
- 7. PATTERN LINEWIDTH IS 0.001" ±0.0001" (0.0254MM ±0.0025MM)
- 8. PATTERN ORIENTATION: RIGHT READING LOOKING THROUGH. PATTERN ON SAME SURFACE AS BEVEL.
- COATING: LOW REFLECTION CHROMIUM FIRST SURFACE. CHROMIUM ADHESION LAYER WITH A TOP LAYER OF CHROMIUM OXIDE, OPTICAL DENSITY > 3.0. COATING DESIGNED TO PROVIDE REFLECTION < 5% @ 550 NM
- 10. PATTERN: HALF SOLID, HALF BRACKET GAUGE. 15 LINEWIDTHS: 0.002" TO 0.016" IN 0.001" INCREMENTS
- 11. PACKAGING: BAG AND TAG PER 700MLA0060-001
- 12. PATTERN DIAMETER: 16.592MM

MILO PART NUMBER: AA023		EDMOND P/N: 30587 OI		NLINE CATALOG RD2055
TOLERANCES (EXCEPT AS NOTED)	MAX LEVY AUTOGRAPH			
DECIMAL .XXX= +/005	SODA LIME GLASS		SCALE	DRAWN BY TEN
.XX= +/015			NONE	APPROVED BY
.X= +/030				
FRACTIONAL	TITLE			
+/030	THICKNESS GAUGE .002" TO .016"			
ANGULAR	DATE	DRAWING NUMBER		
+/-0 5Deg	12-15-00	300MLA0062A-005		