

OXIDE, OPTICAL DENSITY > 3.0. COATING DESIGNED TO PROVIDE REFLECTION < 5% @ 550 NM 10. PATTERN: 10MM RADIUS SCALE NUMBERED EVERY MM; GRADUATED EACH 0.5MM 180° PROTRACTOR NUMBERED EVERY 10°, GRADUATED EACH DEGREE

CHROMIUM ADHESION LAYER WITH A TOP LAYER OF CHROMIUM

9. COATING: LOW REFLECTION CHROMIUM FIRST SURFACE.

- 11. ANGULAR ACCURACY: ±1 ARC SECOND
- 12. PACKAGING: BAG AND TAG PER 700MLA0060-001
- 13. PATTERN DIAMETER: 24.387MM

NOTES:

WILO PART NO	VIDER. AAUZ4	EDIVIDIND F/N. 3	USOS CIN	LINE CATALOG IND2000
TOLERANCES (EXCEPT AS NOTED)	MAX LEVY AUTOGRAPH			
.XXX= +/005 .XX= +/015 .X= +/030	SODA LIM	E GLASS	NONE	TEN  APPROVED BY
FRACTIONAL	METRIC RADIUS SCALE WITH			
+/030	PROTRACTOR			
aNgular +/-0.5Deg.	12-15-00	300	MLA(	0062A-006

AUTH

CK