

- 1. BEVEL: 0.9MM AT 45° MAX
- 2. SURFACE FLATNESS: 3-4 WAVES
- 3. SURFACE QUALITY: SCRATCH:DIG 20:10 OVER ACTIVE AREA
- 4. PARALLELISM: < 30 ARCSEC
- 5. PERPENDICULARITY: 0.00004" (0.001MM)
- 6. PATTERN TO BE CENTERED ON SUBSTRATE ±0.004" (±0.10MM)
- 7. PATTERN LINEWIDTH IS 0.001" ±0.0001" (0.0254MM ±0.0025MM)
- 8. PATTERN ORIENTATION: RIGHT READING LOOKING THROUGH. PATTERN ON SAME SURFACE AS BEVEL.
- 9. COATING: LOW REFLECTION CHROMIUM FIRST SURFACE. CHROMIUM ADHESION LAYER WITH A TOP LAYER OF CHROMIUM OXIDE, OPTICAL DENSITY > 3.0. COATING DESIGNED TO PROVIDE REFLECTION < 5% @ 550 NM
- 10. PATTERN: CROSSLINE HAIRS
- 11. PACKAGING: BAG AND TAG PER 700MLA0060-001
- 12. PATTERN DIAMETER: 27.00MM

| MLO PART NUMBER: AA026 | | EDMUND P/N: 39443 | | ONLINE CATALOG | RD2055 |
|---------------------------------|---------------------|-------------------|-------|----------------|--------|
| TOLERANCES (EXCEPT AS NOTED) | MAX LEVY AUTOGRAPH | | | | |
| DECIMAL .XXX= +/005 | MATERIAL | | SCALE | DRAWN BY TEN | |
| .XX= +/015 .X= +/030 | | ME GLASS | NONE | APPROVED BY | |
| FRACTIONAL | TITLE | | | | |
| +/030 | CROSSHAIR | | | | |
| ANGULAR | DATE DRAWING NUMBER | | | | |
| +/-0.5Deg. | 12-15-00 | 300MLA0062A-008 | | | |