

MAX LEVY AUTOGRAPH, INC. PROPRIETARY

- 1. BEVEL: 0.9MM AT 45° MAX
- 2. SURFACE FLATNESS: 3-4 WAVES
- 3. SURFACE QUALITY: SCRATCH:DIG 20:10 OVER ACTIVE AREA
- 4. PARALLELISM: < 30 ARCSEC
- 5. PATTERN OVERALL DIMESIONAL ACCURACY: 0.00004" (0.001MM)
- 6. PATTERN TO BE CENTERED ON SUBSTRATE ±0.004" (±0.10MM)
- 7. PATTERN LINEWIDTH IS 0.001" ±0.0001" (0.0254MM ±0.0025MM)
- 8. PATTERN ORIENTATION: RIGHT READING LOOKING THROUGH. PATTERN ON SAME SURFACE AS BEVEL.
- 9. COATING: LOW REFLECTION CHROMIUM FIRST SURFACE. CHROMIUM ADHESION LAYER WITH A TOP LAYER OF CHROMIUM OXIDE, OPTICAL DENSITY > 3.0. COATING DESIGNED TO PROVIDE REFLECTION < 5% @ 550 NM
- 10. PATTERN: 0 TO 360° IN 1° INCREMENTS
- 11. PACKAGING: BAG AND TAG PER 700MLA0060-001
- 12. ANGULAR ACCURACY: ±1 ARC SECOND
- 13. PATTERN DIAMETER: 24.395MM

MLO PART NUMBER: AA034		EDMUND P/N: 39455		ONLINE CATALOG RD2055
TOLERANCES (EXCEPT AS NOTED)	MAX LEVY AUTOGRAPH			
DECIMAL .XXX= +/005	MATERIAL		SCALE	DRAWN BY TEN
.XX= +/015 .X= +/030	SODA LIME GLASS		NONE	APPROVED BY
FRACTIONAL	TITLE			
+/030	360° PROTRACTOR WITH CROSSHAIR			
ANGULAR +/-0.5Deg.	12-18-00	300	ML	A0062A-016

SYM

REVISION RECORD

AUTH

CK