

MAX LEVY AUTOGRAPH, INC. PROPRIETARY

NOTES:

- 1. BEVEL: 0.9MM AT 45° MAX
- 2. SURFACE FLATNESS: 3-4 WAVES
- 3. SURFACE QUALITY: SCRATCH:DIG 20:10 OVER ACTIVE AREA
- 4. PARALLELISM: < 30 ARCSEC
- 5. PATTERN OVERALL DIMESIONAL ACCURACY: 0.00004" (0.001MM)
- 6. PATTERN TO BE CENTERED ON SUBSTRATE ±0.004" (±0.10MM)
- 7. PATTERN LINEWIDTH IS 0.001" ±0.0001" (0.0254MM ±0.0025MM)
- 8. PATTERN ORIENTATION: RIGHT READING LOOKING THROUGH. PATTERN ON SAME SURFACE AS BEVEL.
- 9. COATING: LOW REFLECTION CHROMIUM FIRST SURFACE. CHROMIUM ADHESION LAYER WITH A TOP LAYER OF CHROMIUM OXIDE, OPTICAL DENSITY > 3.0. COATING DESIGNED TO PROVIDE REFLECTION < 5% @ 550 NM
- 10. PATTERN: 5 CONCENTRIC SQUARES; (MM) 2, 4, 6, 8, 10.
- 11. PACKAGING: BAG AND TAG PER 700MLA0060-001
- 12. PATTERN DIAMETER: 14.812MM

MLO PART NU	MBER: AA041	EDMUND P/N: 39466		ONL	INE CATALOG	RD2055
TOLERANCES (EXCEPT AS NOTED)	MAX LEVY AUTOGRAPH					
DECIMAL .XXX= +/005	MATERIAL		SCALE		DRAWN BY TEN	
.XX= +/015 .X= +/030	SODA LIN	/IE GLASS	NONE	Ì	APPROVED BY	<u>-</u>
FRACTIONAL					408484 18	
	™ METRIC SQUARES, 2 TO 10MM IN 2MM					
+/030	INCREMENTS					
ANGULAR	DATE	DRAWING NUMBER				
+/-0.5Deg.	12-18-00 300MLA0062A-023					