

NOTES:

- 1 BEVEL: REMOVE SHARP EDGES
- 2. SURFACE FLATNESS: 3-4 WAVES
- 3. SURFACE QUALITY: SCRATCH:DIG 20:10 OVER ACTIVE AREA
- 4. PARALLELISM: < 30 ARCSEC
- 5. PERPENDICULARITY: 0.00004" (0.001MM)
- 6. PATTERN TO BE CENTERED ON SUBSTRATE ±0.004" (±0.10MM)
- 7. PATTERN LINEWIDTH IS 0.001" ±0.0001" (0.0254MM ±0.0025MM)
- 8. PATTERN ORIENTATION: RIGHT READING LOOKING THROUGH.
- 9. COATING: LOW REFLECTION CHROMIUM FIRST SURFACE.
 CHROMIUM ADHESION LAYER WITH A TOP LAYER OF CHROMIUM
 OXIDE, OPTICAL DENSITY > 3.0. COATING DESIGNED TO PROVIDE
 REFLECTION < 5% @ 550 NM
- 10. PATTERN: CROSSHAIR LINES
- 11. PACKAGING: BAG AND TAG PER 700MLA0060-001
- 12. PATTERN DIAMETER: 26.00MM

MLO PART NUMBER: AA043			01	NLINE CATALOG	RD2055
TOLERANCES (EXCEPT AS NOTED)	MAX LEVY AUTOGRAPH				
DECIMAL .XXX= +/005	MATERIAL		SCALE	DRAWN BY TEN	
.XX= +/015	SODA LIME GLASS		NONE	APPROVED BY	
.X= +/030					
FRACTIONAL	TITLE				
+/030	CROSSHAIR				
ANGULAR	DATE	DRAWING NUMBER		0000	004
+/-0.5Deg.	1-8-01 3000MLA0069A-001				