

NOTES:

- 1. BEVEL: REMOVE SHARP EDGES
- 2. SURFACE FLATNESS: 3-4 WAVES
- 3. SURFACE QUALITY: SCRATCH:DIG 20:10 OVER ACTIVE AREA
- 4. PARALLELISM: < 30 ARCSEC
- 5. PATTERN OVERALL DIMESIONAL ACCURACY: 0.00004" (0.001MM)
- 6. PATTERN TO BE CENTERED ON SUBSTRATE ±0.004" (±0.10MM)
- 7. PATTERN LINEWIDTH IS 0.0002" ±0.00004" (0.005MM ±0.001MM)
- 8. PATTERN ORIENTATION: RIGHT READING LOOKING THROUGH.
- 9. COATING: LOW REFLECTION CHROMIUM FIRST SURFACE. CHROMIUM ADHESION LAYER WITH A TOP LAYER OF CHROMIUM OXIDE, OPTICAL DENSITY > 3.0. COATING DESIGNED TO PROVIDE REFLECTION < 5% @ 550 NM
- 10. PATTERN: STRAIGHT LINE RULE WITH INCH TOP AND METRIC BOTTOM. INCH: 0 TO 0.90" IN 0.002" INCREMENTS.
- METRIC: 0 TO 23MM IN 0.05MM INCREMENTS.

 11. PACKAGING: BAG AND TAG PER 700MLA0060-001
- 12. PATTERN DIAMETER: 23.568MM

MLO PART NUMBER: AA048			ON	ILINE CATALOG	RD2055
TOLERANCES (EXCEPT AS NOTED)	MAX LEVY AUTOGRAPH				
DECIMAL .XXX= +/005 .XX= +/015 .X= +/030	SODA LIM	ME GLASS	NONE	DRAWN BY TEN APPROVED BY	
FRACTIONAL +/030	CALIBRATION RULE .002" / .050MM				
+/-0.5Deg.	01/09/01 DRAWING NUMBER 300MLA0069A-006				