

## NOTES:

- 1. BEVEL: REMOVE SHARP EDGES.
- 2. SURFACE FLATNESS: 3-4 WAVES
- 3. SURFACE QUALITY: SCRATCH:DIG 20:10 OVER ACTIVE AREA
- 4. PARALLELISM: < 30 ARCSEC
- 5. PATTERN OVERALL DIMESIONAL ACCURACY: 0.00004" (0.001MM)
- 6. PATTERN TO BE CENTERED ON SUBSTRATE ±0.004" (±0.10MM)
- 7. PATTERN LINEWIDTH IS 0.001" ±0.0001" (0.0254MM ±0.0025MM)
- 8. PATTERN ORIENTATION: RIGHT READING LOOKING THROUGH.
- COATING: LOW REFLECTION CHROMIUM FIRST SURFACE. CHROMIUM ADHESION LAYER WITH A TOP LAYER OF CHROMIUM OXIDE, OPTICAL DENSITY > 3.0. COATING DESIGNED TO PROVIDE REFLECTION < 5% @ 550 NM</li>
- 10. PATTERN: HALF SOLID BAR, HALF BRACKET GAUGE.
  15 LINEWIDTHS: (MM) 0.02-0.10 IN 0.01 INCREMENTS, 0.15, 0.20, 0.25, 0.30, 0.35, 0.40.
- 11. PACKAGING: BAG AND TAG PER 700MLA0060-001
- 12. PATTERN DIAMETER: 16.030MM

MLO PART NUMBER: AA055			0	NLINE CATALOG	RD2055
TOLERANCES (EXCEPT AS NOTED)	MAX LEVY AUTOGRAPH				
DECIMAL .XXX= +/005 .XX= +/015 .X= +/030	SODA	LIME GLASS	SCALE NONE	DRAWN BY TEN APPROVED BY	
+/030	THICKNESS GAUGE .02MM TO .40MM				
+/-0.5Deg.	01/09/01 RAWING NUMBER 300MLA0069A-013				