

NOTES:

- 1. BEVEL: REMOVE SHARP EDGES.
- 2. SURFACE FLATNESS: 3-4 WAVES
- 3. SURFACE QUALITY: SCRATCH:DIG 20:10 OVER ACTIVE AREA
- 4. PARALLELISM: < 30 ARCSEC
- 5. PATTERN OVERALL DIMESIONAL ACCURACY: 0.00004" (0.001MM)
- 6. PATTERN TO BE CENTERED ON SUBSTRATE ±0.004" (±0.10MM)
- 7. PATTERN LINEWIDTH IS 0.001" ±0.0001" (0.0254MM ±0.0025MM)
- 8. PATTERN ORIENTATION: RIGHT READING LOOKING THROUGH.
- 9. COATING: LOW REFLECTION CHROMIUM FIRST SURFACE. CHROMIUM ADHESION LAYER WITH A TOP LAYER OF CHROMIUM OXIDE, OPTICAL DENSITY > 3.0. COATING DESIGNED TO PROVIDE REFLECTION < 5% @ 550 NM
- 10. PATTERN: 10MM RADIUS SCALE NUMBERED EVERY MM, GRADUATED EACH 0.5MM. 180° PROTRACTOR NUMBERED EVERY 10°, GRADUATED EACH DEGREE.
- 11. ANGULAR ACCURACY: ±1 ARC SECOND
- 12. PACKAGING: BAG AND TAG PER 700MLA0060-001
- 13. PATTERN DIAMETER: 22.292MM

MLO PART NUMBER: AA058			OI	NLINE CATALOG	RD2055
TOLERANCES (EXCEPT AS NOTED)	MAX LEVY AUTOGRAPH				
DECIMAL .XXX= +/005	MATERIAL		SCALE	DRAWN BY TEN	
.XX= +/015 .X= +/030	SODA LI	ME GLASS	NONE	APPROVED BY	
FRACTIONAL	TITLE				
+/030	METRIC RADIUS SCALE WITH PROTRACTOR				
aNgular +/-0.5Deg.	01/09/01	300N	/ILA	0069A-	016