

## NOTES:

- 1. BEVEL: REMOVE SHARP EDGES.
- 2. SURFACE FLATNESS: 3-4 WAVES
- 3. SURFACE QUALITY: SCRATCH:DIG 20:10 OVER ACTIVE AREA
- 4. PARALLELISM: < 30 ARCSEC
- 5. PATTERN OVERALL DIMESIONAL ACCURACY: 0.00004" (0.001MM)
- 6. PATTERN TO BE CENTERED ON SUBSTRATE ±0.004" (±0.10MM)
- 7. PATTERN LINEWIDTH IS 0.0004" ±0.00004" (0.01MM ±0.001MM)
- 8. PATTERN ORIENTATION: RIGHT READING LOOKING THROUGH.
- COATING: LOW REFLECTION CHROMIUM FIRST SURFACE. CHROMIUM ADHESION LAYER WITH A TOP LAYER OF CHROMIUM OXIDE, OPTICAL DENSITY > 3.0. COATING DESIGNED TO PROVIDE REFLECTION < 5% @ 550 NM</li>
- 10. PATTERN:
  - SCALES ON BOTH HORIZONTAL AND VERTICAL LINES. 22MM IN 0.1MM INCREMENTS -11MM TO +11MM
- 11. PACKAGING: BAG AND TAG PER 700MLA0060-001
- 12. PATTERN DIAMETER: 22.578MM

MLO PART NUMBER: AA062				ONLINE CATALOG RD2055
TOLERANCES (EXCEPT AS NOTED)	MAX LEVY AUTOGRAPH			
DECIMAL .XXX= +/005 .XX= +/015 .X= +/030	SODA LIME GLASS		SCALE	DRAWN BY TEN APPROVED BY
FRACTIONAL +/030	CALIBRATION CROSS LINE SCALE 1MM INCREMENTS			
aNgular +/-0.5Deg.	01/09/01 BRAWING NUMBER 300MLA0069A-020			