

NOTES:

- 1 BEVEL REMOVE SHARP EDGES.
- 2. SURFACE FLATNESS: 3-4 WAVES
- 3. SURFACE QUALITY: SCRATCH:DIG 20:10 OVER ACTIVE AREA
- 4. PARALLELISM: < 30 ARCSEC
- 5. PATTERN OVERALL DIMESIONAL ACCURACY: 0.00004" (0.001MM)
- 6. PATTERN TO BE CENTERED ON SUBSTRATE ±0.004" (±0.10MM)
- 7. PATTERN LINEWIDTH IS 0.001" ±0.0001" (0.0254MM ±0.0025MM)
- 8. PATTERN ORIENTATION: RIGHT READING LOOKING THROUGH.
- COATING: LOW REFLECTION CHROMIUM FIRST SURFACE. CHROMIUM ADHESION LAYER WITH A TOP LAYER OF CHROMIUM OXIDE, OPTICAL DENSITY > 3.0. COATING DESIGNED TO PROVIDE REFLECTION < 5% @ 550 NM
- 10. PATTERN:

16 SETS OF CIRCLES. DRILL AND TAP SIZE MEASUREMENTS TO INCLUDE: M1.0 TO M7.0. OUTER DIAMETER OF TAP GAUGE INDICATES NOMINAL THREAD O.D.

- 11. PACKAGING: BAG AND TAG PER 700MLA0060-001
- 12. PATTERN DIAMETER: 21.655MM

MLO PART NUMBER: AA063			10	NLINE CATALOG RD2055
TOLERANCES (EXCEPT AS NOTED)	MAX LEVY AUTOGRAPH			
DECIMAL .XXX= +/005 .XX= +/015	SODA LIM	E GLASS	SCALE	TEN
.X= +/030		L OLAGO		APPROVED BY
+/030	THREAD GAUGE INCH			
ANGULAR +/-0.5Deg.	01-09-01 DRAWING NUMBER 300MLA0069-021			