

NOTES:

- 1. BEVEL: REMOVE SHARP EDGES.
- 2. SURFACE FLATNESS: 3-4 WAVES
- 3. SURFACE QUALITY: SCRATCH:DIG 20:10 OVER ACTIVE AREA
- 4. PARALLELISM: < 30 ARCSEC
- 5. PATTERN OVERALL DIMENSIONAL ACCURACY: 0.00004" (0.001MM)
- 6. PATTERN TO BE CENTERED ON SUBSTRATE ±0.004" (±0.10MM)
- 7. PATTERN LINEWIDTH IS 0.001" ±0.0001" (0.0254MM ±0.0025MM)
- 8. PATTERN ORIENTATION: RIGHT READING LOOKING THROUGH.
- 9. COATING: LOW REFLECTION CHROMIUM FIRST SURFACE. CHROMIUM ADHESION LAYER WITH A TOP LAYER OF CHROMIUM OXIDE, OPTICAL DENSITY > 3.0. COATING DESIGNED TO PROVIDE REFLECTION < 5% @ 550 NM
- 10. PATTERN: 0.75" STRAIGHT LINE RULE. 0 TO 0.75" IN 0.005" INCREMENTS, NUMBERED EVERY 0.025".
- 11. PACKAGING: BAG AND TAG PER 700MLA0060-001 12. PATTERN DIAMETER: 19.460MM

MLO PART NUMBER: AA079			0	NLINE CATALOG	RD2055
TOLERANCES (EXCEPT AS NOTED)	MAX LEVY AUTOGRAPH				
DECIMAL .XXX= +/005	MATERIAL		SCALE	DRAWN BY TEN	
.XX= +/015 .X= +/030	SODA LIME GLASS		NONE	APPROVED BY	
FRACTIONAL	TITLE				
+/030	STRAIGHT LINE RULE, 0-0.75" / .005" INCREMENTS				
+/-0.5Deg.	01/03/01 DRAWING NUMBER 300MLA0070A-012				