

NOTES:

- 1. BEVEL: REMOVE SHARP EDGES.
- 2. SURFACE FLATNESS: 3-4 WAVES
- 3. SURFACE QUALITY: SCRATCH:DIG 20:10 OVER ACTIVE AREA
- 4. PARALLELISM: < 30 ARCSEC
- 5. PATTERN OVERALL DIMENSIONAL ACCURACY: 0.00004" (0.001MM)
- 6. PATTERN TO BE CENTERED ON SUBSTRATE ±0.004" (±0.10MM)
- 7. PATTERN ORIENTATION: RIGHT READING LOOKING THROUGH.
- COATING: LOW REFLECTION CHROMIUM FIRST SURFACE. CHROMIUM ADHESION LAYER WITH A TOP LAYER OF CHROMIUM OXIDE, OPTICAL DENSITY > 3.0. COATING DESIGNED TO PROVIDE REFLECTION < 5% @ 550 NM
- 9. PATTERN:
 - 15 LINE WIDTHS: 0.02MM-0.10MM; 0.15MM; 0.20MM; 0.025MM; 0.30MM; 0.35MM; 0.40MM.
- 10. PACKAGING: BAG AND TAG PER 700MLA0060-001
- 11. PATTERN DIAMETER: 16.030MM

MLO PART NUMBER: AA080			10	ILINE CATALOG	RD2055
TOLERANCES (EXCEPT AS NOTED)	MAX LEVY AUTOGRAPH				
DECIMAL .XXX= +/005	MATERIAL		SCALE	DRAWN BY TEN	
.XX= +/015 .X= +/030	SODA LI	ME GLASS	NONE	APPROVED BY	
FRACTIONAL	TITLE				
+/030	THICKNESS GAUGE .02MM TO .40MM				
ANGULAR	DATE	DRAWING NUMBER	41 A C	0704	040
+/-0.5Deg.	12/20/00 300MLA0070A-013				