

- 2. SURFACE FLATNESS: 3-4 WAVES
- 3. SURFACE QUALITY: SCRATCH:DIG 20:10 OVER ACTIVE AREA
- 4. PARALLELISM: < 30 ARCSEC
- 5. PATTERN OVERALL DIMENSIONAL ACCURACY: 0.00004" (0.001MM)
- 6. PATTERN TO BE CENTERED ON SUBSTRATE ±0.004" (±0.10MM)
- 7. PATTERN LINEWIDTH IS 0.001" ±0.0001" (0.0254MM ±0.0025MM)
- 8. PATTERN ORIENTATION: RIGHT READING LOOKING THROUGH.
- COATING: LOW REFLECTION CHROMIUM FIRST SURFACE. CHROMIUM ADHESION LAYER WITH A TOP LAYER OF CHROMIUM OXIDE, OPTICAL DENSITY > 3.0. COATING DESIGNED TO PROVIDE REFLECTION < 5% @ 550 NM</li>
- 10. PATTERN:
- 0 TO 360° PROTRACTOR IN 1° INCREMENTS, NUMBERED EVERY 10°
- 11. ANGULAR ACCURACY: ±1 ARC SECOND
- 12. PACKAGING: BAG AND TAG PER 700MLA0060-001
- 13. PATTERN DIAMETER: 22.422MM

MLO PART NUMBER: AA082			OI	NLINE CATALOG	RD2055
TOLERANCES (EXCEPT AS NOTED)	MAX LEVY AUTOGRAPH				
DECIMAL XXX= +/005	MATERIAL		SCALE	DRAWN BY TEN	
.XX= +/015	SODA LIME GLASS		NONE	APPROVED BY	
.X= +/030					
FRACTIONAL	TITLE		-	*	
+/030	PROTRACTOR, 1° INCREMENTS				
ANGULAR	DATE	DRAWING NUMBER			
+/-0.5Deg.	12/19/00 300MLA0070A-015				