

NOTES:

- 1. BEVEL: REMOVE SHARP EDGES.
- 2. SURFACE FLATNESS: 3-4 WAVES
- 3. SURFACE QUALITY: SCRATCH:DIG 20:10 OVER ACTIVE AREA
- 4. PARALLELISM: < 30 ARCSEC

MAX LEVY AUTOGRAPH, INC. PROPRIETARY

- 5. PATTERN OVERALL DIMENSIONAL ACCURACY: 0.00004" (0.001MM)
- PATTERN TO BE CENTERED ON SUBSTRATE ±0.004" (±0.10MM)
- 7. PATTERN LINEWIDTH IS 0.001" ±0.0001" (0.0254MM ±0.0025MM)
- 8. PATTERN ORIENTATION: RIGHT READING LOOKING THROUGH.
- 9. COATING: LOW REFLECTION CHROMIUM FIRST SURFACE. CHROMIUM ADHESION LAYER WITH A TOP LAYER OF CHROMIUM OXIDE, OPTICAL DENSITY > 3.0. COATING DESIGNED TO PROVIDE REFLECTION < 5% @ 550 NM
- 10. PATTERN:

10MM RADIUS SCALE NUMBERED EVERY MM; GRADUATED EACH 0.5MM; 180° PROTRACTOR NUMBERED EVERY 10°; GRADUATED EACH DEGREE

- 11. ANGULAR ACCURACY: ±1 ARC SECOND
- 12. PACKAGING: BAG AND TAG PER 700MLA0060-001
- 13. PATTERN DIAMETER: 22.292MM

MLO PART NUMBER: AA083				ONLINE CATALOG	RD2055
TOLERANCES (EXCEPT AS NOTED)	MAX LEVY AUTOGRAPH				
DECIMAL .XXX= +/005 .XX= +/015	SODA LIME GLASS		SCALE NONE	DRAWN BY TEN APPROVED BY	
.X= +/030 FRACTIONAL	TITLE				
+/030	METRIC RADIUS SCALE WITH PROTRACTOR				
+/-0.5Deg.	12/20/00	300N	/ILA	0070A-	016