

NOTES:

- 1. BEVEL: REMOVE SHARP EDGES.
- 2. SURFACE FLATNESS: 3-4 WAVES
- 3. SURFACE QUALITY: SCRATCH:DIG 20:10 OVER ACTIVE AREA
- 4. PARALLELISM: < 30 ARCSEC
- 5. PATTERN OVERALL DIMENSIONAL ACCURACY: 0.00004" (0.001MM)
- 6. PERPENDICULARITY: 0.00004" (0.001MM)
- 7. PATTERN TO BE CENTERED ON SUBSTRATE ±0.004" (±0.10MM)
- 8. PATTERN LINEWIDTH IS 0.001" ±0.0001" (0.0254MM ±0.0025MM)
- 9. PATTERN ORIENTATION: RIGHT READING LOOKING THROUGH.
- COATING: LOW REFLECTION CHROMIUM FIRST SURFACE. CHROMIUM ADHESION LAYER WITH A TOP LAYER OF CHROMIUM OXIDE, OPTICAL DENSITY > 3.0. COATING DESIGNED TO PROVIDE REFLECTION < 5% @ 550 NM
- 11. PATTERN
- 20 CONCENTRIC CIRCLES CENTERED ON CROSSHAIRS. 0 TO 20MM IN 1MM INCREMENTS.
- 12. PACKAGING: BAG AND TAG PER 700MLA0060-001
- 13. PATTERN DIAMETER: 20.950MM

MLO PART NUMBER: AA085				ONLINE CATALOG RD2055
TOLERANCES (EXCEPT AS NOTED)	MAX LEVY AUTOGRAPH			
DECIMAL XXX= +/005	MATERIAL		SCALE	DRAWN BY TEN
.XX= +/015	SODA LIME GLASS		NONE	APPROVED BY
.X= +/030				
FRACTIONAL	TITLE			
+/030	CONCENTRIC CIRCLES 1MM INCREMENTS / CROSSHAIR			
ANGULAR	DATE	DRAWING NUMBER		
+/-0.5Deg.	12/28/00 300MLA0070A-018			

AUTH DR CK