

## NOTES:

- 1. BEVEL: REMOVE SHARP EDGES.
- 2. SURFACE ACCURACY: 3-4 WAVES
- 3. SURFACE QUALITY: SCRATCH:DIG 20:10 OVER ACTIVE AREA
- 4. PARALLELISM: < 30 ARCSEC

MAX LEVY AUTOGRAPH, INC. PROPRIETARY

- 5. PATTERN OVERALL DIMENSIONAL ACCURACY: 0.00004" (0.001MM)
- 6. PATTERN TO BE CENTERED ON SUBSTRATE ±0.004" (±0.10MM)
- 7. PATTERN LINEWIDTH IS 0.0004" ±0.00004" (0.01MM ±0.001MM)
- 8. PATTERN ORIENTATION: RIGHT READING LOOKING THROUGH
- COATING: LOW REFLECTION CHROMIUM FIRST SURFACE. CHROMIUM ADHESION LAYER WITH A TOP LAYER OF CHROMIUM OXIDE, OPTICAL DENSITY > 3.0.
  COATING DESIGNED TO PROVIDE REFLECTION < 5 % @ 550 NM</li>
- 10. PATTERN: SCALES ON BOTH HORIZONTAL AND VERTICAL CROSSLINES. 22MM IN 0.1MM INCREMENTS. NUMBERED EVERY 1MM. -11MM 0 +11MM
- 11. PACKAGING: BAG AND TAG PER 700MLA0060-001
- 12. PATTERN DIAMETER: 22.578MM

MLO PART NUMBER: AA087			10	NLINE CATALOG	RD2055	
TOLERANCES (EXCEPT AS NOTES	M	MAX LEVY AUTOGRAPH				
.XXX= +/005		W.4E OL 4.00	SCALE	DRAWN BY TEN		
.XX= +/015 .X= +/030	SODAL	IME GLASS	NONE	APPROVED BY		
FRACTIONAL	TITLE			1		
+/030	CALIBRAT	CALIBRATION CROSS LINE SCALE, .1MM INCREMENTS				
ANGULAR	DATE	DRAWING NUMBER	41 A C		000	
+/-0.5Deg.	12/20/00	12/20/00 300MLA0070A-020				