

AA088

NOTES:

- BEVEL: REMOVE SHARP EDGES.
- 2. SURFACE FLATNESS: 3-4 WAVES
- 3. SURFACE QUALITY: SCRATCH:DIG 20:10 OVER ACTIVE AREA
- 4. PARALLELISM: < 30 ARCSEC
- 5. PATTERN OVERALL DIMESIONAL ACCURACY: 0.00004" (0.001MM)
- 6. PATTERN TO BE CENTERED ON SUBSTRATE ±0.004" (±0.10MM)
- 7. PATTERN LINEWIDTH IS 0.001" ±0.0001" (0.0254MM ±0.0025MM)
- 8. PATTERN ORIENTATION: RIGHT READING LOOKING THROUGH.
- 9. COATING: LOW REFLECTION CHROMIUM FIRST SURFACE. CHROMIUM ADHESION LAYER WITH A TOP LAYER OF CHROMIUM OXIDE, OPTICAL DENSITY > 3.0. COATING DESIGNED TO PROVIDE REFLECTION < 5% @ 550 NM

10. PATTERN:

16 SETS OF CIRCLES. DRILL AND TAP SIZE MEASUREMENTS TO INCLUDE: M1.0 TO M7.0. OUTER DIAMETER OF TAP GAUGE INDICATES NOMINAL THREAD O.D.

MADE IN THE USA

- 11. PACKAGING: BAG AND TAG PER 700MLA0060-001
- 12. PATTERN DIAMETER: 21.655MM

MLO PART NUMBER: AA088			10	NLINE CATALOG	RD2055
TOLERANCES (EXCEPT AS NOTED)	MAX LEVY AUTOGRAPH				
DECIMAL .XXX= +/005	MATERIAL		SCALE	DRAWN BY RJS	
.XX= +/015	SEE NOTES		NONE	APPROVED BY	
.X= +/030					
FRACTIONAL	TITLE		•	*	
+/030	THREAD GAUGE INCH				
+/-0.5Deg.	12/19/00	300	MLA	0070-0)21

-1.50mm±0.10mm [0.059"±0.004"]

AUTH DR CK