

- 4. PARALLELISM: < 30 ARCSEC
- 5. PATTERN OVERALL DIMENSIONAL ACCURACY: 0.00004" (0.001MM)
- 6. PATTERN TO BE CENTERED ON SUBSTRATE ±0.004" (±0.10MM)
- 7. PATTERN LINEWIDTH IS 0.001" ±0.0001" (0.0254MM ±0.0025MM)
- 8. PATTERN ORIENTATION: RIGHT READING LOOKING THROUGH
- COATING: LOW REFLECTION CHROMIUM FIRST SURFACE. CHROMIUM ADHESION LAYER WITH A TOP LAYER OF CHROMIUM OXIDE, OPTICAL DENSITY > 3.0. COATING DESIGNED TO PROVIDE REFLECTION < 5 % @ 550 NM
- 10. PATTERN:

 0.3° X 0.4° GRID IN 0.025° SQUARES. TWO HORIZONTAL SCALES; 0.4° WITH 0.005° DIVISIONS; 20MM WITH 0.10MM DIVISIONS. ANGLESCALE 0° TO 90° IN 1° DIVISIONS. RADIUS SCALE 1 TO 10MM. NINE CIRCLES 0.1MM TO 0.7MM, 1.5MM AND 3.0MM DIAMETER.

- 11. ANGULAR ACCURACY: ±1 ARC SECOND
- 12. PACKAGING: BAG AND TAG PER 700MLA0060-001
- 13. PATTERN DIAMETER: 22.250MM

MLO PART NUMBER: AA091			ON	LINE CATALOG	RD2055
TOLERANCES (EXCEPT AS NOTED)	MA	OGRAP	Н		
DECIMAL .XXX= +/005 .XX= +/015	SODA I	IME GLASS	SCALE NONE	DRAWN BY TEN APPROVED BY	
.X= +/030 FRACTIONAL	TITLE				
+/030	ENG. GRID & METRIC SCALE / CIRCLES / PROTRACTOR				
+/-0.5Deg.	12/26/00	300N	/ILAO	070A-	024