
MAX LEVY AUTOGRAPH, INC. PROPRIETARY THIS DRAWING CONTAINS CONFIDENTIAL PROPRIETARY INFORMATION THAT IS MAX LEVY AUTOGRAPH, INC. PROPERTY. DO NOT DISCLOSE NOR DUPLICATE FOR OTHERS EXCEPT AS AUTHORIZED BY MAX LEVY AUTOGRAPH, INC.	DATE	SYM	REVISION RECORD	AUTH	DR	СК
	9/13/01	А	CONVERTED TO ACAD, ADDED MLO PART NO.S			



## NOTES:

MLO PART NUMBER:

NEGATIVE TARGET: DA014

POSITIVE TARGET: DA015

- 1. SUBSTRATE: 2" X 2" (50.8 X 50.8MM) PHOTO QUALITY SELECT SODA LIME GLASS, INDEX OF REFRACTION 1.512 / 1.523 (0.5893MM, SODIUM D LINE). ALTERNATES B270, SW SUPER WHITE CROWN, C1 CROWN, OR EQUIVALENT. NOMINAL THICKNESS 1.5MM (1.27/1.78MM).
- 2. FLATNESS: 0.0025MM / 25.4MM OR BETTER.
- 3. OPTICAL QUALITY: SCRATCH/DIG <=20/10
- 4. COATING: CHROMIUM REFLECTIVITY 50 % ±5%. OPTICAL DENSITY >3.0. NO PINHOLES IN THE COATING ARE ACCEPTABLE LARGER THAN 0.025MM A MAXIMUM FIVE PINHOLES ON ANY ONE TARGET MAY BE REPAIRED WITH BLACK EPOXY INK.
- 5. EDGES: BREAK SHARP EDGES. THERE SHALL BE NO VISIBLE EDGE CHIPS LARGER THAN 0.25MM DIAMETER.
- 6. TARGET CONFIGURATION: FREQUENCY RANGE FROM 1-18 CYCLES/MM.
- 7. TARGET IS PACKAGED IN GARY PLASTIC CONTAINER PART NO. G-803 (3 1/2" X 2 9/16" X 1/2") WITH TWO FOAM INSERTS.
- 8. LINEWIDTH TOLERANCE: ±0.0005MM

DWG DASH NUMBER:

NEGATIVE TARGET: -003

POSITIVE TARGET: -004

ONLINE CATALOG RD2055

TOLERANCES (EXCEPT AS NOTED)	MAX LEVY AUTOGRAPH								
DECIMAL .XXX= +/005	MATERIAL		SCALE	DRAWNBY					
.XX= +/015 .X= +/030	SEE NOTES	8	NONE	APPROVED BY					
FRACTIONAL +/030	NBS 19	S 1963A RESOLUTION TARGET							
+/-0.5Deg.	8/18/92	110M	LA00	24A-00X					